

**LCDL10-3**  
10W 880-960Lm  
Warm White 3000K  
60° Dimmable

**LCDL10-4**  
10W 880-960Lm  
Cool White 4000K  
60° Dimmable

## Low Glare LED Downlight

Low glare, recessed residential & commercial

100mm, 90-95mm cut out, switchable colour, dimmable  
Low glare recessed Downlight for residential, commercial applications.



### Specifications

Lumen Output	880 - 950lm
Input Power	10W
Beam Angle	60 Deg.
Hole Cutout Size	90 - 95mm
CCT	Warm White 3000K / Cool White 4000K
Trim Colour	White RAL9016 Trim - Black RAL9005 Heatsink
Warranty	3yr
IP Rating	IP54
IC Rating	IC-4
Supply Input	220-240V, 50/60Hz
Driver	External
Power Factor	>0.9
Useful life @Ta25° (L70)	50,000hr
Dimensions	Ø100 x 90.6mm
Operating Ambient Temp.	-25 to 50°C
Electrical Classification	Class 2
Housing	Aluminium + Heatsink
Connection Type	0.6m Flex & Plug
Total Weight	0.47kg

### Features

Unique model design, anti-glare led downlight with deep recessed reflector.

Uses supreme ADC12 aluminium heat sink with great heat dissipation and light distribution.

External isolater driver.

Dimmable.

High lumen 2835 SMD led chip with antiglare PMMA lens, up to 100lm/w.

Front IP54, IK10 rated.